

SHOCK ABSORBER OIL - SHOWA

Shock absorber oil especially made for SHOWA

Description

SHOCK ABSORBER OIL - SHOWA is formulated from highly refined group II base oils, a highly shear stable Viscosity Index Improver and an additive package including rust, oxidation, and corrosion inhibitors.

Applications

SHOCK ABSORBER OIL - SHOWA is used as working media in shock absorbers of motorcycle, passenger cars, light duty, heavy duty trucks, and other commercial vehicles.

Specification Meets

- ▶ DIN 51 524, Part 3
- ▶ ISO 11158-HV
- ▶ ISO 6743/4 & ISO L-HV

Advantages

- ▶ Very good thermal and mechanical stability
- ▶ Excellent low temperature performance
- ▶ Excellent anti-oxidant properties for high temperature resistance to increase life time
- ▶ Contains anti-friction additive especially designed to provide smooth movements
- ▶ Fast acting anti-foam additive for maximum damping efficiency
- ▶ Low volatility
- ▶ Representing the seal protection

Typical Data of SHOCK ABSORBER OIL - SHOWA

Characteristics	Unit	SHOCK ABSORBER OIL - SHOWA	Test Method
Appearance		Bright and clear	Visual
Color		Red	ASTM D 1500
Density @ 15 °C	kg/L	0.8732	ASTM D 4052
Kinematic Viscosity @ 40 °C	cSt	36.15	ASTM D 445
Kinematic Viscosity @ 100 °C		6.58	
Viscosity Index		138	ASTM D 2270
Flash Point (COC)	°C	226	ASTM D 92
Pour Point	°C	-39	ASTM D 97

* the typical characteristic mentioned represent mean values