

FETT CHS-3

Premium quality chassis grease

Description

As a time tested Calcium based grease that is fortified with a smooth stinky texture, **FETT CHS-3** has good adhesion to metal surfaces, great water wash-out resistance, and good displacement under shock loads & vibrations.

Applications

- ▶ Recommended for all types of chassis lubrication requirements such as ball joints, suspensions, steering systems, plain bearings, bushings, and pins in automotive chassis assemblies, even in wet operating conditions
- ▶ Also recommended for slow rotating slide bearings and articulations where wide variety of outdoor and inland marine requirements are necessary
- ▶ In wide range of outdoor applications where contacts with water are frequent, **FETT CHS-3** is also suitable as a non "EP" general purpose grease

Specification Meets:

FETT CHS-3 meets the ISO 6743-9: L-XBAHA 3 and DIN 51 502: M2/3C-20 specification.

Advantages

- ▶ Great Water Wash-Out resistance
- ▶ Great rust and corrosion protection
- ▶ Good and trusted equipment reliability and availability
- ▶ Balanced lubrication properties ensure longer service life
- ▶ Great protection against dirt and moisture contamination
- ▶ Controlled oil release

Typical Data of FETT CHS-3

Characteristics	Unit	FETT CHS-3	Test Method
NLGI Grade		3	
Color		Brown	Visual
Texture		Smooth & Tacky	Visual
Base Oil		Mineral	
Soap Type		Calcium	
Kinematic Viscosity @ 40°C	cSt	100	ASTM D 445
Drop Point, min	°C	95	ASTM D 566
Worked Penetration, 60 strokes @ 25 °C	dmm	220-250	ASTM D 217

* the typical characteristic mentioned represent mean values